

## Steel Strap – Strapping Tools



## Steel strap – strapping tools

### Manual tools for flat surfaced packages



#### CH 47

Every function per hand lever, stamp seals, without metal seal. Suitable for all types of strap. Strap width: 12,7 - 19,0mm, Strap thickness: 0,38 - 0,63mm. Weight: 3,5kg.



#### CH 48

Every function per hand lever, stamp seals, without metal seal. Suitable for all types of strap. Strap width: 19,0mm, Strap thickness: 0,63 - 0,80mm. Weight: 5,2kg.



#### CM 14

Every function per hand lever, with metal seals in a magazine. suitable for all types of strap. Strap width: 12,7/16mm, Strap thickness: 0,40 - 0,63mm. Weight: 4,5kg.



### Compressed air tools for flat surfaced packages

#### CH 45-20/21

Every function per push button. Stamp seals, without metal seal. Suitable for all types of strap. Strap width: 12,7 - 19,0mm, Strap thickness: 0,50 - 0,80mm. Tension force: 4.000 - 6.500N Weight: 9,7 / 11,5kg.

### Manual tools for round or irregularly formed packages



#### Wide strap spanner B Sealer WZ

Transport wheel spanner with clipping edge. Safety sealer with 2(4) notches. Suitable for all types of strap. Strap width: 19,0 - 32,0mm, Strap thickness: max. 1,0mm. Weight: 3,7kg / 2,4kg



#### Rondofix 1(V) Sealer VZ

2 tools for tensioning and sealing. The metal seal beading per hand. Strap type: Uniflex Strap width: 12,7 - 16,0mm (Strap width: 19,0 - 25,0mm), Strap thickness: max. 0,6 (0,8) mm Weight: 1,8kg

### Compressed air tools for round or irregularly formed packages



#### PN 6.1 / PVO

Tensioning and sealer tool for wide straps. Suitable for all types of strap. Strap width: 19,0 - 32,0mm, Strap thickness: max. 1,0mm. Tension force: 8.000N Weight: 4,3/3,4kg.



#### CR 24A / 25A / 26A

Every function per push button. Suitable for all types of strap. Strap width: 12,7 - 32,0mm Strap thickness: 0,63-1,00mm Tension force: 3.300 - 8.400N Weight: 3,3 / 7,0 / 9,3kg

### Accessories for steel strap strapping tools



QPW



ST/2



BB

### Maintenance unit

Required for operation with compressed air tools. The maintenance unit consists of a water separator, manometer and lubricator.

### Spring balancer

For the weightless working with strapping tools.

3,5 - 6,5 kg  
7,5 - 11,5 kg  
13,0 - 25,0 kg

### Strap dispenser

Type	Strap	Strap width	Coil/Ring measurements		
			inner	outer	width
QPW	Ribbon wound steel strap (PW)	9,5 - 19,0	400	600	75
ST/2	Wound steel strap (ES)	12,7 - 19,0	400	600	19
BB	Wound wide steel strap (ES)	25,0 - 32,0	440	660	25/32

Subject to modifications  
© Copyright 2006 by Cyklop GmbH

Cyklop GmbH, Postfach 50 12 20  
50972 Köln, Deutschland  
Industriestraße 133, Rodenkirchen,  
50996 Köln, Deutschland

Telefon: ++49 (0) 2236 / 602 0  
Fax Vertrieb: ++49 (0) 2236 / 602 578  
www.cyklop.de,  
info@cyklop.de

**CYKLOP**  
INTERNATIONAL

THE  
STRAPPING  
COMPANY  
Update 05/2006