



CR 19

BATTERY-DRIVEN STEEL STRAPPING TOOL

CYKLOP[®]
GLOBAL PACKAGING SOLUTIONS

STRAPPING
WRAPPING
CODING
TAPING

The CR 19 delivers highspeed operation for steel strapping applications. Complete with an ergonomic design and several features, the CR 19 helps to improve productivity anywhere it is needed.

The CR 19 provides an electronically controlled and reproducible strapping process. It has an intuitive touchscreen user interface and allows a quick and comfortable adjustment of the strapping parameters, selectabel in manual, semi of fully- automatic operations modes.

Through visual and auditory signals, the real time strapping status indicator helps the user to achieve a perfect seal.

The 4Ah battery is can be used for up to 500 cycles per battery charge, allowing continuous operation, with full mobility throughout the plant, unrestricted by the reach of air hoses or air quality.



Options

- User interface cover
- Suspension bracket for stationary use



Technical specifications

Operation mode	auto / semi / manual
Tension force	400 - 3.000 N
Tension speed	135 mm/s
Dimensions (LxWxH)	390 x 150 x 140 mm
Consumable	Steel strap
Strap thickness	0,4 - 0,63 mm
Strap width	13, 16, 19 mm
Strap tensile strength	1.100 N max.
Sealing method	Seal joint - single notch
Battery	Bosch Li-Ion ProCORE 18 V/4Ah
Strapping / battery	Up to 500 cycles / charge
Weight	4,5 kg
Operating temperature	-10 °C to +40 °C
Battery charger voltage	230V

Cyklop International
 Industriestraße 133, D-50996 Köln
 (Rodenkirchen)
 Postfach / P.O. Box 50 12 20,
 D-50972 Köln (Rodenkirchen)

+49 (0) 2236 6020
www.cyklop.com
info@cyklop.com

CYKLOP[®]
 GLOBAL PACKAGING SOLUTIONS

STRAPPING
 WRAPPING
 CODING
 TAPING