



CR 32

STEEL STRAPPING TOOL

CYKLOP[®]
GLOBAL PACKAGING SOLUTIONS

STRAPPING
WRAPPING
CODING
TAPING

The CR 32 is a robust battery driven steel strapping tool and is suitable for 19, 25 and 32 mm steel strap. The CR 32 can be used for both horizontal and vertical straps, making the device efficient to use. Manual tensioning and closing with seals of steel strap require minimal effort with this model tensioner. The CR 32 is suitable for heavy applications, as it can tension up to 7500 N. The tool has handy carrying handles for easy use.

Advantages

- For steel strap 19, 25, 32 mm
- Horizontal and vertical strapping
- Robust, for heavy applications
- Tensions up to 7,500 N

Options

- Protective cover display
- Bottom protection plate
- Suspension bracket for stationary use



Technical specifications

Weight	8.3 kg
Dimensions (LxWxH)	405 x 283 x 270 mm
Sealing method	Sealjoint with double notch
Tension	2.000 - 7.500 N
Tension speed	75 mm/s
Seal efficiency	approx. 75% of strap tensile strength
Operating temperature	-10 °C to +40 °C
Battery	Bosch Li-Ion ProCORE 18 V/4 Ah, 18 V/8 Ah
Power supply	100 / 110 / 230 V
Charging time	approx. 80 min.
Strapping / battery	Up to 600
Strapping material	Steel strap
Dimensions strapwidth	19, 25 , 32 mm

Cyklop International
 Industriestraße 133, D-50996 Köln
 (Rodenkirchen)
 Postfach / P.O. Box 50 12 20,
 D-50972 Köln (Rodenkirchen)

+49 (0) 2236 6020
www.cyklop.com
info@cyklop.com

