



CR 32

BATTERY-DRIVEN STEEL STRAPPING TOOL

CYKLOP[®]
GLOBAL PACKAGING SOLUTIONS

STRAPPING
WRAPPING
CODING
TAPING

The CR 32 delivers high-speed operation for heavy duty steel strapping applications. Complete with an ergonomic design and several features, the CR 32 helps to improve productivity anywhere it is needed.

The CR 32 provides an electronically controlled and reproducible strapping process. It has an intuitive touchscreen user interface and allows a quick and comfortable adjustment of the strapping parameters, selectable in manual, semi or fully operation modes.

Through visual and auditory signals, the real time strapping status indicator helps the user to achieve a perfect seal.

The 8Ah battery can be used for up to 400 cycles per battery charge, allowing continuous operation with full mobility throughout the plant, not restricted by the reach of air hoses or air quality.



Options

- User interface cover
- Suspension bracket for stationary use



Technical specifications

Operation mode	auto / semi / manual
Tension force	2.000 - 7.500 N
Tension speed	75 mm/s
Dimensions (LxWxH)	405 x 283 x 270 mm
Consumable	Steel strap
Strap thickness	0,6 - 1,0 mm
Strap width	19, 25, 32 mm
Strap tensile strength	1.100 N max.
Sealing method	Seal-joint - double notch
Battery	Bosch Li-Ion ProCORE 18 V/4Ah (8Ah option)
Strapping / battery	Up to 200 (8Ah - 400) cycles / charge
Weight	8,3 kg
Operating temperature	-10 °C to +40 °C
Battery charger voltage	230V

Cyklop International
 Industriestraße 133, D-50996 Köln
 (Rodenkirchen)
 Postfach / P.O. Box 50 12 20,
 D-50972 Köln (Rodenkirchen)

+49 (0) 2236 6020
www.cyklop.com
info@cyklop.com

CYKLOP[®]
 GLOBAL PACKAGING SOLUTIONS

STRAPPING
 WRAPPING
 CODING
 TAPING