



# CSR 9120

STRETCH WRAPPER

**CYKLOP**<sup>®</sup>  
GLOBAL PACKAGING SOLUTIONS

STRAPPING  
WRAPPING  
CODING  
TAPING

The pallet wrapper CSR 9120 can be easily integrated into an existing or new line. This film wrapper ensures that the total costs in your production line will decrease due to the use of film with a high pre-stretch percentage and the very high working speed.

The CSR 9120 is a maintenance-friendly machine, it can wrap up to 120 pallets per hour and the film is easy to replace with the fast-loading system. A corner mount can be added to the machine for extra strength.

**Advantages**

- 2 column portal with moving ring
- External pre-stretch, without electric sliding contacts, pre-stretch 160% to 300%
- Processes up to 120 pallets per hour
- Wrapping speed 65 rpm
- Very accessible film trolley
- Ability to stack inside the ring
- Equipped with fall protection for very fast shutdown

**Options**

- Acid protection
- For loads up to 3000 mm high
- Automatic roll change
- Jumbo rolls
- Pressure plate
- Twin version for 25% higher capacity
- Corner applicator
- Enlarged ring for large loads up to 1,600 x 1,600 mm
- Pallet lifter
- Seal unit with contrastplate
- Top sheet dispenser (inside)



[> Click here for a video of the CSR 9120 <](#)

Technical data:	
Total power installed	12 kW - 13 kW with topsheet
Standard power supply	400 V - 50 Hz - 3 PH+N+G
Protection on electric system	IP 54
Max. pallet dimensions	1200 x 1200 mm
Standard pallet height	2000 mm
Max. rotation speed	65 rpm
Capacity per hour	Up to 120 pallets per hour
Operation pressure	6 Bar

Cyklop International  
 Industriestraße 133  
 D-50996 Köln  
 (Rodenkirchen)  
 Germany

+49 2236 6020  
[www.cyklop.com](http://www.cyklop.com)  
[info@cyklop.com](mailto:info@cyklop.com)

