



CT 102 SD

CASE SEALER

CYKLOP[®]
GLOBAL PACKAGING SOLUTIONS

STRAPPING
WRAPPING
CODING
TAPING

Taping is the application of adhesive tape to, for example, a box or other surface. In the packaging industry, tape is often used to close something, in most cases a box or package. In addition, tape is also used to bundle products, to mark or to communicate a message or to prevent theft.

The ultimate goal of taping is to store and/or ship your products without damage, so that they arrive at your customer in perfect condition. Packaging tape or adhesive tape can be applied manually, with a table dispenser or by machine with a box sealer.

Semi-automatic machine

The CT 102 SD is a high-quality entry-level semi-automatic tape machine suitable for 50 mm PP tape. The machine is supplied without front and rear roller conveyors, but these are available as an option.

After filling the box, the operator closes the flaps and manually feeds the box into the machine. After this, the bottom and top are automatically closed with tape.

The machine can be easily adjusted manually to the required box width and height. The boxes are transported by means of motorised side conveyors, which align the boxes perfectly and guarantee a good seal.

With the CT 102 SD it is possible to professionally close dozens of packages per day.



Standard version of the CT 102 SD

Options:

- Front and rear conveyors
- Castor wheels

[< Click here for a video of the CT 102 SD >](#)

Technical data:	
Dimensions machine (HxWxD)	1.237 x 1.620 x 804 mm
Working height (with wheels 140 mm)	600 - 800 mm
Closing	Top and bottom
Consumable	PP tape
Tape - outer diameter	350 mm (max)
Tape - core diameter	76 mm
Tape - width	50 mm
Package dimension - length	min 150 mm - max ∞
Package dimension - width	150 mm - 500 mm
Package dimension - height	120 mm - 500 mm
Capacity	100 packages / hour
Transport	Side - 20 meter / minute
Protection	IP 54
Power supply	230 V / 50 Hz / 1 phase / 450 Watt
Weight	131 kg



CT 102 with conveyors and castor wheels

Cyklop International
 Industriestraße 133,
 D-50996 Köln
 (Rodenkirchen)
 Germany

+49 2236 6020
www.cyklop.com
info@cyklop.com

