

**CASE SEALER** 



**CT 202 SD CASE SEALER** 

Taping is the application of an adhesive tape on, for example, a box or other surface. In the packaging industry, tape is often used to close something, in most cases a box or package. In addition, tape is also used to bundle products, to mark, to communicate a message or to prevent theft.

The ultimate goal of taping is to store and/or send your products without damage, so that they end up in perfect condition with your customer. Packaging tape can be applied manually, with a table dispenser or with a case sealer.

## Sealing of (only) the bottom

The CT 202 SD is a semi-automatic case sealer suitable for PP or PVC tape from 25 mm to 50 mm. After folding the box, the operator inserts the box manually into the machine. The bottom is then automatically sealed with tape and the box is ready to be filled.

The machine can easily be adjusted manually to the required width. The boxes are transported by means of motorized side conveyor belts, so that the boxes are perfectly aligned and a good seal is guaranteed.

With the CT 202 SD it is possible to professionally prepare hundreds of packages per day so that they can be filled.



## **Options:**

- 67 cm package width
- 75 mm tape width
- Stainless steel version
- Direct printing / coding / labelling
- Extra transport / roller conveyors



Technical data:	
Machine dimensions (H x W x D)	900 x 895 x 81,5 mm
Closure	Bottom
Consumables	PP / PVC tape
Tape - outer roll diameter	360 mm (max)
Tape - core diameter	76 mm
Tape - width	25 - 50 mm
Package size - length	min 150 mm - max ∞
Package size - width	100 mm - 500 mm
Package size - height	100 mm - max ∞
Capacity	800 packages / hour
Transport	Side transport - 22 meters / hour
Protection	IP 54
Power supply	380 V / 50 Hz / 3 phases
Weight	110 kg

Cyklop International Industriestraße 133, D-50996 Köln (Rodenkirchen) Postfach / P.O. Box 50 12 20, D-50972 Köln (Rodenkirchen)

