



CT 203 TBD

CASE SEALER

CYKLOP[®]
GLOBAL PACKAGING SOLUTIONS

STRAPPING
WRAPPING
CODING
TAPING

Taping is the application of adhesive tape to, for example, a box or other surface. In the packaging industry, tape is often used to seal something, in most cases a box or package. In addition, tape is also used to bundle products, to mark products, to communicate a message or to prevent theft.

The ultimate goal of taping is to store and / or ship your products without damage, so that they arrive at your customer in perfect condition. Packaging tape or adhesive tape can be applied manually, with a table dispenser or by machine.

Machine with top and bottom transport

The CT 203 TBD is a semi-automatic case sealer suitable for PP or PVC tape from 25 mm to 50 mm. The CT 203 TBD is particularly suitable for long, narrow boxes, as there are 4 horizontal conveyor belts, two at the top and two at the bottom, running parallel to the tape heads.

After filling the box, the operator folds the top cover and inserts the box manually. Then the top and bottom are automatically closed with tape. The machine can easily be manually adjusted to the required height and width, which is good when the box size to be processed changes little.

With the CT 203 TBD it is possible to professionally close hundreds of packages per day.



Options:

- 67 cm package width
- 75 mm tape width
- Wheels
- Extra transport / roller conveyors
- Direct printing / coding / labeling

Technical data:	
Machine dimensions (H x W x D)	1693 x 1162 x 87,3 mm
Closure	Top and bottom
Consumable	PP / PVC tape
Tape - outer diameter	360 mm (max)
Tape - core diameter	76 mm
Tape - width	25 - 50 mm
Package - length	min 150 mm - max ∞
Package - width	140 mm - 520 mm
Package - height	100 mm - 520 mm
Capacity	1.000 packages / hour
Transport	Top and bottom, 22 meter / hour
Protection	IP 54
Power supply	380 V / 50 Hz / 3 phases
Weight	152 kg



Cyklop International
 Industriestraße 133, D-50996 Köln
 (Rodenkirchen)
 Postfach / P.O. Box 50 12 20,
 D-50972 Köln (Rodenkirchen)

+49 (0) 2236 6020
www.cyklop.com
info@cyklop.com

