

**CASE SEALER** 



CT 305 TBR CASE SEALER

In the packaging industry, tape is often used to seal boxes. Taping is therefore of great importance in the damage free storage and shipping of your products, so they arrive at your customer in perfect condition. Taping machines from Cyklop ensure a reliable and efficient taping process and are easy to set up and operate. The (semi-)automatic taping machines can be operated separately but are also perfectly integrable with other Cyklop machines in your packaging line.

The CT 305 TBR is an automatic case sealer suitable for PP and PVC tape and perfectly designed for low boxes or heigh boxes with a small footprint.

The machine starts automatically by feeding the box into the case sealer which automatically adapts the centering device and the height to different box dimensions. This makes the box closing process easy and efficient. When a box enters the machine, the bottom and top are automatically closed with tape. The top and bottom drive belts ensure a stable transportation and a perfect box sealing.

With the CT 305 TBR, it is possible to professionally close thousands of packages per day.



Standard version of the CT 305 TBR

## **Options:**

- Caster wheels
- Tape end / breakage detection
- Flexible scissor roller conveyor



Inside view of CT 305 TBR

Technical data:	CT 305 TBR	CT 305 TBR 65
Box length (mm)	150 - ∞	150 - ∞
Box width (mm)	140 - 510	165 - 660
Height (mm)	100 - 510	110 - 660
Performance (Boxes/h)	Up to 450 boxes/h	
Box sealing	Top and Bottom	
Conveyor height	650 - 750 mm	
Conveyor speed	24 m/min	
Compressed air	6 bar	
Air consumption	5 NI/ cycle	7 Nl/ cycle
Power supply	400V/50Hz/3Ph/0,22kW	
Tape	PP or PVC tape	
Tape width	50 mm (optional 75 mm)	
Machine dimensions LxWxH (mm)	1390x971x1629	1390x1121x1818
Machine weight (kg)	160	180

