



**CTT 215**

**PALLETWRAPPER**

**CYKLOP**<sup>®</sup>  
GLOBAL PACKAGING SOLUTIONS

STRAPPING  
WRAPPING  
CODING  
TAPING

The CTT215 wraps irregular loads without any problems. The properties of this wrapping machine include not only good loading costs, but also low material costs due to minimal film consumption. With the CTT 215 you have the opportunity to get the most ideal stretch out of the wrapping film. This gives a professional and tightly wrapped pallet. In addition, you can adjust the speed of the palletwrapper and adjust the tension on the pallet.

**Costsaving**

The unique ‚power-ecostretch‘ pre-stretch system can achieve a pre-stretch of up to 300%. From 1 meter of film, 4 meters of film will be made, which can result in cost and environmental savings of up to 65%. In this way, the CTT 215 quickly pays for itself. The pre-stretching rollers in the film carriage are motorized. This means that (very) light and vulnerable pallets can also be wrapped stably at low costs per pallet.

In addition, the pallet wrapper is a very sustainable choice because of the aluminum mast, robust carriage and wheels under the turntable.



[> Click here for a video of the CTT 215 <](#)

**Options**

- Larger table
- Extended mast
- Ramp (for pump truck)
- Integrated scale
- Film cutting unit
- Other options upon request

Technical data:	
Turntable	Ø1650 mm
Max. pallet dimensions (LxWxH)	1200 x 1000 x 2200 mm
Max. pallet weight	2000 kg
Wrapping speed	12 rpm
Pre-stretch	30% - 300%
Programs	5 standard, 1 option
Wrapping film	Core 76 mm
	Outer diameter 250 mm
	Width 500 mm
Protection	IP54
Control	PLC
Power supply	200-240 V / 50-60 Hz / 1 phase / 10 A
Weight	380 kg

Cyklop International  
 Industriestraße 133, D-50996 Köln  
 (Rodenkirchen)  
 Postfach / P.O. Box 50 12 20,  
 D-50972 Köln (Rodenkirchen)

+49 (0) 2236 6020  
[www.cyklop.com](http://www.cyklop.com)  
[info@cyklop.com](mailto:info@cyklop.com)

