



M PAC HE

STRAPPING MACHINE

**CYKLOP**<sup>®</sup>  
GLOBAL PACKAGING SOLUTIONS

STRAPPING  
WRAPPING  
CODING  
TAPING

The semi-automatic strapping machine M-PAC HE is suitable for horizontally strapping of pallets or, for example, auction trolleys. The machine can be used for strapping relatively small amounts of pallets or carts per day.

**Advantages**

- Strapping up to 2210 mm in height
- For PP strap of 12 or 15.5 mm
- Up to 690 N strapping tension
- Closure with welding tongue
- Mobile, so it can be used anywhere
- Stepless adjustment of strapping head
- Remote control for operation of the machine

**Options**

- Battery for more flexibility



[< CLICK HERE FOR A VIDEO OF THE M PAC HE >](#)



Technical specifications	
Min. package size	Approx. 170 mm (H)
Strapping material	PP strap 12 or 15,5 mm
Strap coil	Core diameter: 200 mm Outer diameter: 420 mm Width: 190 mm
Strap tension	Max. 690 N
Heating time	Approx. 30 sec.
Sealing	Heat-seal
Supply voltage	230 V, 50 Hz or battery
Machine weight	Approx. 160 kg
Machine height	2830 mm

Cyklop International  
 Industriestraße 133  
 D-50996 Köln  
 (Rodenkirchen)  
 Germany

+49 2236 6020  
[www.cyklop.com](http://www.cyklop.com)  
[info@cyklop.com](mailto:info@cyklop.com)

